# cisco



## Cisco IP Phone 8841



The Cisco<sup>®</sup> IP Phone 8841 is a business-class collaboration endpoint that delivers high-fidelity, reliable, secure, and scalable voice communication for small to large enterprise businesses.

With the Cisco IP Phone 8841, you can increase personal productivity through an engaging user experience that is both powerful and easy-to-use. The IP Phone 8841 combines an attractive new ergonomic design with wideband audio for crystal clear voice communications, "always-on" reliability, encrypted voice communications to enhance security, and access to a comprehensive suite of unified communication features from Cisco on-premises and hosted infrastructure platforms and third party hosted call control.

The Cisco IP Phone 8841 offers five programmable line keys. You can configure keys to support either multiple directory numbers or call features such as speed dial. You can also boost productivity by handling multiple calls for each directory number, using the multicall-per-line feature. Fixed function keys give you one-touch access to applications, messaging, directory, as well as often-used calling features such as hold/resume, transfer, and conference. Backlit acoustic keys provide flexibility for audio path selection and switching.

Other key features of the phone follow:

- The Cisco IP Phone 8841 offers a 5-in. high-resolution (800 x 480) widescreen VGA backlit color display. Localized language support, including right-to-left on-screen text, meets the needs of global users.
- The phone supports a built-in Gigabit Ethernet switch for your PC connection.
- Support for Cisco EnergyWise<sup>™</sup> technology makes the Cisco IP Phone 8841 more energy-efficient and ecofriendly; the phone is qualified by Energy Star organization.
- · An optional wall-mount kit is orderable as a spare part for customers seeking this capability.

#### **Features and Benefits**

Table 1 lists features and benefits of the Cisco IP Phone 8841.

 Table 1.
 Features and Benefits

Features	Benefits
Hardware Features	
Ergonomic design	The phone offers an easy-to-use interface and provides a traditional telephony-like user experience.
Graphical display	The 800 × 480, 24-bit color, 5-in. WVGA display provides scrollable access to calling features and text-based XML applications.
Handset	<ul> <li>The handset is a standard wideband-capable audio handset (connects through an RJ-9 port).</li> <li>The standard coiled cord has a custom end for concealed cable routing beneath the phone (cord length is approximately 21 in. [55 cm] coiled and up to 72 in. (183 cm) extended).</li> <li>The handset is hearing aid-compatible (HAC) and meets Federal Communications Commission (FCC) loudness requirements for the Americans with Disabilities Act (ADA). Section 508 loudness requirements can be achieved using industry-standard inline handset amplifiers such as Walker Equipment W-10 or CE-100 amplifiers. The dial pad is also ADA-compliant.</li> </ul>
Speaker phone	<ul> <li>A full-duplex speakerphone gives you flexibility in placing and receiving calls with hands free. For added security, the audible dual tone multifrequency (DTMF) tones are masked when the speakerphone mode is used.</li> </ul>
Analog headset	The analog headset jack is a standard wideband-capable RJ-9 audio port.
AUX port	You can use an auxiliary port to support electronic hookswitch control with a third-party headset connected to it.
Ethernet switch	<ul> <li>An internal 2-port Cisco Ethernet switch allows for a direct connection to a 10/100/1000BASE-T Ethernet network (IEEE 802.3i/802.3u/802.3ab) through a RJ-45 interface with single LAN connectivity for both the phone and a co-located PC.</li> <li>The system administrator can designate separate VLANs (IEEE 802.1Q) for the PC and phone, providing improved security and reliability of voice and data traffic.</li> </ul>
Keys	The phone has the following keys: Line keys Soft keys Back and release keys Four-way navigation and select keys Hold/Resume, Transfer, and Conference keys Messaging, Application, and Directory keys Standard keypad Volume-control toggle key Speakerphone, headset, and mute keys
Backlit indicator	<ul> <li>The phone supports backlit indicators for the audio path keys (handset, headset, and speakerphone), select key, line keys, and message waiting.</li> </ul>
Replaceable bezel	The phone includes a black bezel; an optional silver bezel is also orderable separately.
Dual-position foot stand	<ul> <li>The display is easy-to-view and the buttons and keys are easy-to-use. The two-position foot stand supports viewing angles of 35 and 50 degrees; you can remove the foot stand for wall mounting, with mounting holes located on the base of the phone.</li> </ul>
Wall-mountable	You can install the phone on a wall using an optional wall-mount kit (orderable separately).
Physical security	The phone is compatible with the Kensington Security Slot (K-Slot) antitheft system.
Power Features	
IEEE Power over Ethernet (PoE)	• IEEE Power over Ethernet class 2. The phone is compatible with both IEEE 802.3af and 802.3at switch blades and supports both Cisco Discovery Protocol and Link Layer Discovery Protocol - Power over Ethernet (LLDP-PoE).
Cisco IP Phone Power Cube 4	<ul> <li>This optional power cube is used as an AC-to-DC (48V) power supply for non-PoE deployments. Use of the power cube 4 also requires the use of one of the corresponding AC country cords.</li> </ul>

Features	Benefits
Call-Control Support	
Cisco Unified Communications Manager	<ul> <li>8.5.1 (Non-secured mode Only)</li> <li>8.6.2</li> <li>9.1.2</li> <li>10.5.2</li> <li>11.0 and later</li> </ul>
Cisco Unified Communications Manager Express (Unified CME)	• 10.0 and later through fast track
Cisco Business Edition 6000 (BE 6000)	<ul> <li>8.6.2</li> <li>9.1.2</li> <li>10.5.2</li> <li>11.0 and later</li> </ul>
Cisco Hosted Collaboration Solution (HCS)	8.6.2 and later (using supported UCM versions above)

## Licensing

The Cisco IP Phone 8841 requires an Enhanced User Connect License (UCL) in order to connect to Cisco Unified Communications Manager.

## **Product Specifications**

Table 2 lists the features and specifications of the Cisco IP Phone 8841.

Table 2. Features and Specifications

Features	Specifications
Audio codec support	G.711a-law and mu-law, G.722, G.729a, Internet Low Bitrate Codec (iLBC), and Internet Speech Audio Codec (iSAC)
Call features	+ Dialing     Abbreviated dialing     Adjustable ring tones and volume levels     Adjustable display brightness     Agent greeting     Auto-answer     Auto-detection of headset     cBarge     Busy Lamp Field (BLF)     Busy Lamp Field (BLF) Pickup     Busy Lamp Field (BLF) Speed dial     Callback     Call forward     Call forward     Call filter     Call history lists     Call pickup     Call timer     Call waiting     Call call caperone     Caller ID     Corporate directory     Conference, including traditional Join feature     Cross Cluster Extension Mobility (EMCC)     Direct transfer

Features	Specifications
	Extension mobility
	Fast-dial service
	Forced access codes and client matter codes
	Group call pickup
	• Hold
	• Intercom
	● Immediate divert
	Malicious-caller ID
	Message-waiting indicator (MWI)
	Meet-me conference
	Mobility
	Music on hold (MoH)
	• Mute
	Network profiles (automatic)
	On- and off-network distinctive ringing
	Personal directory
	• PickUp
	Predialing before sending
	• Privacy
	Private Line Automated Ringdown (PLAR)
	• Redial
	Ring tone per line appearance
	Service Uniform Resource Locator (URL)
	Shared line
	Silent monitoring and recording
	Speed dial
	Time and date display
	Transfer
	Uniform Resource Identifier (URI) dialing
	Visual voice mail
	Voice mail
	Whisper coaching
Electronic hookswitch	You can control the hookswitch electronically with a third-party headset connected to the auxiliary port.
Quality-of-service (QoS) options	The phone supports Cisco Discovery Protocol and 802.1Q/p standards, and can be configured with an 801.1Q VLAN header containing the VLAN ID overrides configured by the Admin VLAN ID.
Network features	Session Initiation Protocol (SIP) for signaling
	Session Description Protocol (SDP)
	• IPv4 and IPv6
	User Datagram Protocol (UDP) (used only for Real-Time Transport Protocol [RTP] streams)
	Dynamic Host Configuration Protocol (DHCP) client or static configuration
	Gratuitous Address Resolution Protocol (GARP)
	Domain Name System (DNS)
	Trivial File Transfer Protocol (TFTP)
	Secure Hypertext Transfer Protocol (HTTPS)
	• VLAN
	Real-Time Transport Protocol (RTP)
	Real-Time Control Protocol (RTCP)
	Cisco Peer-to-Peer Distribution Protocol (PPDP)
	Cisco Discovery Protocol
	• LLDP (including LLDP-MED)
	Switch speed auto-negotiation

Security features  Secure boot Secure credential storage Device authentication Configuration file authentication and encryption Image authentication Random bit generation Hardware cryptographic acceleration Certificate Authority Proxy Function (CAPF) Manufacturer-Installed Certificates (MIC) Locally Significant Certificates (LSC) Ethernet 802.1x supplicant options: Extensible Authentication Protocol-Flexible Authentication via Set Tunneling (EAP-FAST) and Extensible Authentication Protocol-Transport Layer Security (EAP-TLS) Signaling authentication and encryption using TLS Media authentication and encryption using SRTP HTTPS for client and server Secure Shell (SSH) Protocol server Secure Shell (SSH) Protoc	cure
Device authentication Configuration file authentication and encryption Image authentication Random bit generation Hardware cryptographic acceleration Certificate Authority Proxy Function (CAPF) Manufacturer-Installed Certificates (MIC) Locally Significant Certificates (MIC)  Ethernet 802.1x supplicant options: Extensible Authentication Protocol-Flexible Authentication via Set Tunneling (EAP-FAST) and Extensible Authentication Protocol-Transport Layer Security (EAP-TLS) Signaling authentication and encryption using TLS Media authentication and encryption using SRTP HTTPS for client and server Secure Shell (SSH) Protocol server ScL-based VPN client  Physical dimensions (H × W × D)  Weight (with handset) Phone-casing composition Operational temperature  Nonoperational temperature Nonoperational temperature  Operating 10 to 90%, noncondensing	cure
Configuration file authentication and encryption Image authentication Random bit generation Hardware cryptographic acceleration Certificate Authority Proxy Function (CAPF) Manufacturer-Installed Certificates (MIC) Locally Significant Certificates (LSC) Ethernet 802.1x supplicant options: Extensible Authentication Protocol-Flexible Authentication via Ser Tunneling (EAP-FAST) and Extensible Authentication Protocol-Transport Layer Security (EAP-TLS) Signaling authentication and encryption using TLS Media authentication and encryption using SRTP HTTPS for client and server Secure Shell (SSH) Protocol server Sclub ased VPN client  Physical dimensions (H × W × D) Weight (with handset) Phone-casing composition Operational temperature Nonoperational temperature Nonoperational temperature 14 to 140°F (-10 to 60°C) Poperating 10 to 90%, noncondensing	cure
Image authentication     Random bit generation     Random bit generation     Hardware cryptographic acceleration     Certificate Authority Proxy Function (CAPF)     Manufacturer-Installed Certificates (MIC)     Locally Significant Certificates (LSC)     Ethernet 802.1x supplicant options: Extensible Authentication Protocol-Flexible Authentication via Set Tunneling (EAP-FAST) and Extensible Authentication Protocol-Transport Layer Security (EAP-TLS)     Signaling authentication and encryption using TLS     Media authentication and encryption using SRTP     HTTPS for client and server     Secure Shell (SSH) Protocol server     SSL-based VPN client     Physical dimensions (H x W x D)     Weight (with handset)     Phone-casing composition     Operational temperature     Nonoperational temperature     Nonoperational temperature 10 to 90%, noncondensing     Operation 10 to 90%, noncondensing     Operational temperature     Operational temperatu	cure
Random bit generation Hardware cryptographic acceleration Certificate Authority Proxy Function (CAPF) Manufacturer-Installed Certificates (MIC) Locally Significant Certificates (LSC) Ethernet 802.1x supplicant options: Extensible Authentication Protocol-Flexible Authentication via Ser Tunneling (EAP-FAST) and Extensible Authentication Protocol-Transport Layer Security (EAP-TLS) Signaling authentication and encryption using TLS Media authentication and encryption using SRTP HTTPS for client and server Secure Shell (SSH) Protocol server Scure Shell (SSH) Protocol server SSL-based VPN client  Physical dimensions (H × W × D) Weight (with handset) Phone-casing composition  Peolycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A  Operational temperature  Nonoperational temperature  Nonoperational temperature operating 10 to 90%, noncondensing	cure
<ul> <li>Hardware cryptographic acceleration</li> <li>Certificate Authority Proxy Function (CAPF)</li> <li>Manufacturer-Installed Certificates (MIC)</li> <li>Locally Significant Certificates (LSC)</li> <li>Ethernet 802.1x supplicant options: Extensible Authentication Protocol-Flexible Authentication via Set Tunneling (EAP-FAST) and Extensible Authentication Protocol-Transport Layer Security (EAP-TLS)</li> <li>Signaling authentication and encryption using TLS</li> <li>Media authentication and encryption using SRTP</li> <li>HTTPS for client and server</li> <li>Secure Shell (SSH) Protocol server</li> <li>SSL-based VPN client</li> <li>9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm)</li> <li>(excluding foot stand)</li> <li>Weight (with handset)</li> <li>Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A</li> <li>32 to 104°F (0 to 40°C)</li> <li>14 to 140°F (-10 to 60°C)</li> <li>14 to 140°F (-10 to 60°C)</li> <li>Operating 10 to 90%, noncondensing</li> </ul>	cure
Certificate Authority Proxy Function (CAPF)  Manufacturer-Installed Certificates (MIC)  Locally Significant Certificates (LSC)  Ethernet 802.1x supplicant options: Extensible Authentication Protocol-Flexible Authentication via Sec Tunneling (EAP-FAST) and Extensible Authentication Protocol-Transport Layer Security (EAP-TLS)  Signaling authentication and encryption using TLS  Media authentication and encryption using SRTP  HTTPS for client and server  Secure Shell (SSH) Protocol server  SSL-based VPN client  Physical dimensions (H × W × D)  Weight (with handset)  Phone-casing composition  Operational temperature  Nonoperational temperature  Nonoperational temperature  Operating 10 to 90%, noncondensing	cure
Manufacturer-Installed Certificates (MIC)     Locally Significant Certificates (LSC)     Ethernet 802.1x supplicant options: Extensible Authentication Protocol-Flexible Authentication via Secturnneling (EAP-FAST) and Extensible Authentication Protocol-Transport Layer Security (EAP-TLS)     Signaling authentication and encryption using TLS     Media authentication and encryption using SRTP     HTTPS for client and server     Secure Shell (SSH) Protocol server     SEL-based VPN client  Physical dimensions (H × W × D)  Weight (with handset)  Phone-casing composition  Operational temperature  Nonoperational temperature  Nonoperational temperature  Operating 10 to 90%, noncondensing	cure
Locally Significant Certificates (LSC)     Ethernet 802.1x supplicant options: Extensible Authentication Protocol-Flexible Authentication via Sectrunneling (EAP-FAST) and Extensible Authentication Protocol-Transport Layer Security (EAP-TLS)     Signaling authentication and encryption using TLS     Media authentication and encryption using SRTP     HTTPS for client and server     Secure Shell (SSH) Protocol server     SEL-based VPN client  Physical dimensions (H × W × D)  Weight (with handset)  Phone-casing composition  Operational temperature  Nonoperational temperature  Nonoperational temperature  Operating 10 to 90%, noncondensing	cure
Ethernet 802.1x supplicant options: Extensible Authentication Protocol-Flexible Authentication via Sec Tunneling (EAP-FAST) and Extensible Authentication Protocol-Transport Layer Security (EAP-TLS)     Signaling authentication and encryption using TLS     Media authentication and encryption using SRTP     HTTPS for client and server     Secure Shell (SSH) Protocol server     SEL-based VPN client  Physical dimensions (H × W × D)  Weight (with handset)  Phone-casing composition  Operational temperature  Nonoperational temperature  Nonoperational temperature  Pethone of the protocol Flexible Authentication Protocol-Flexible Authentication Protocol-Fl	cure
Tunneling (EAP-FAST) and Extensible Authentication Protocol-Transport Layer Security (EAP-TLS)  Signaling authentication and encryption using TLS  Media authentication and encryption using SRTP  HTTPS for client and server  Secure Shell (SSH) Protocol server  SSL-based VPN client  Physical dimensions (H × W × D)  Weight (with handset)  Phone-casing composition  Operational temperature  Nonoperational temperature  Nonoperational temperature shock  Humidity  Tunneling (EAP-FAST) and Extensible Authentication Protocol-Transport Layer Security (EAP-TLS)  9 Signaling authentication and encryption using TLS  Nedia authentication and encryption using SRTP  HTTPS for client and server  9 Secure Shell (SSH) Protocol server  9 Secure Shell (SSH) Protocol server  9 SSL-based VPN client  9 9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm)  (excluding foot stand)  9 2.58 lb (1.17 kg)  Phone-casing composition  9 Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A  9 32 to 104°F (0 to 40°C)  9 14 to 140°F (-10 to 60°C)  9 14 to 140°F (-10 to 60°C)	cure
Media authentication and encryption using SRTP     HTTPS for client and server     Secure Shell (SSH) Protocol server     SSL-based VPN client  Physical dimensions (H × W × D)  Weight (with handset)  Phone-casing composition  Operational temperature  Nonoperational temperature  Mumidity  Media authentication and encryption using SRTP  Protocol server  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  Phone-casing composition  9.2.58 lb (1.17 kg)  Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A  Operational temperature  Nonoperational temperature  Operating 10 to 90%, noncondensing	
HTTPS for client and server     Secure Shell (SSH) Protocol server     SSL-based VPN client  Physical dimensions (H × W × D)  Weight (with handset)  Phone-casing composition  Operational temperature  Nonoperational temperature  Humidity  HTTPS for client and server  9 Secure Shell (SSH) Protocol server  9 SSL-based VPN client  9 202 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9 2.58 lb (1.17 kg)  Phone-casing composition  9 Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A  Operational temperature  9 32 to 104°F (0 to 40°C)  9 14 to 140°F (-10 to 60°C)  9 Operating 10 to 90%, noncondensing	
Secure Shell (SSH) Protocol server     SSL-based VPN client  Physical dimensions (H x W x D)  Weight (with handset)  Phone-casing composition  Operational temperature  Nonoperational temperature  Secure Shell (SSH) Protocol server  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excludi	
SSL-based VPN client  Physical dimensions (H × W × D)  Weight (with handset)  Phone-casing composition  Operational temperature  Nonoperational temperature shock  Publication of SSL-based VPN client  Polyca 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)  Polyca 2.58 lb (1.17 kg)  Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A  Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A  Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A  Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A  Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A  Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A  Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A  Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A  Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A  Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A  Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A  Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A  Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A  Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A  Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A	
Physical dimensions (H × W × D)  Weight (with handset)  Phone-casing composition  Operational temperature  Nonoperational temperature  Nonoperational temperature  Humidity  • 9.02 × 10.13 × 1.57 in. (229.1 × 257.34 × 40 mm) (excluding foot stand)  • 2.58 lb (1.17 kg)  • Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A  • 32 to 104°F (0 to 40°C)  • 14 to 140°F (-10 to 60°C)  • 14 to 140°F (-10 to 60°C)	
(H x W x D)  (excluding foot stand)  (excluding foot stand)  • 2.58 lb (1.17 kg)  Phone-casing composition  Operational temperature  Nonoperational temperature shock  Humidity  • (excluding foot stand)  • 2.58 lb (1.17 kg)  • Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A  • 32 to 104°F (0 to 40°C)  • 14 to 140°F (-10 to 60°C)  • 14 to 140°F (-10 to 60°C)	
Phone-casing composition Operational temperature  Nonoperational temperature shock  Humidity  • Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A  • 32 to 104°F (0 to 40°C)  • 14 to 140°F (-10 to 60°C)  • Operating 10 to 90%, noncondensing	
Operational temperature  • 32 to 104°F (0 to 40°C)  Nonoperational temperature shock  Humidity  • 32 to 104°F (0 to 40°C)  • 14 to 140°F (-10 to 60°C)  • Operating 10 to 90%, noncondensing	
Nonoperational temperature shock  Humidity  • 14 to 140°F (-10 to 60°C)  • Operating 10 to 90%, noncondensing	
temperature shock  Humidity  • Operating 10 to 90%, noncondensing	
<ul> <li>Nonoperating 10 to 95%, noncondensing</li> </ul>	
Language support • Arabic (Arabic Area)	
Bulgarian (Bulgaria)	
Catalan (Spain)	
Chinese (China)	
Chinese (Hong Kong)	
Chinese (Taiwan)	
Croatian (Croatia)	
Czech (Czech Republic)	
Danish (Denmark)      The state of the	
• Dutch (Netherlands)	
• English (United Kingdom)	
• Estonian (Estonia)	
French (France) French (Canada)	
• Finnish (Finland)	
• German (Germany)	
• Greek (Greece)	
Hebrew (Israel)	
Hungarian (Hungary)	
• Italian (Italy)	
• Japanese (Japan)	
• Latvian (Latvia)	
• Lithuanian (Lithuania)	
Korean (Korea Republic)	
Norwegian (Norway)	
Polish (Poland)	
Portuguese (Portugal)	
Portuguese (Brazil)	

Features	Specifications
	Romanian (Romania)
	Russian (Russian Federation)
	Spanish (Columbia)
	Spanish (Spain)
	Slovak (Slovakia)
	Swedish (Sweden)
	Serbian (Republic of Serbia)
	Serbian (Republic of Montenegro)
	Slovenian (Slovenia)
	• Thai (Thailand)
	• Turkish (Turkey)

## **Product Specifications**

Table 3 gives ordering information for the phone and its accessories.

 Table 3.
 Ordering Information

Product Number	Description
CP-8841-K9=	Cisco IP Phone 8841, Charcoal
CP-8841-W-K9=	Cisco IP Phone 8841, White
CP-DX-HS=	Spare Handset for Cisco 7800, 8800, DX600 Series, Charcoal
CP-DX-CORD=	Spare Handset Cord for Cisco 8800, DX600 Series, Charcoal
CP-DX-W-HS=	Spare Handset for Cisco IP Phone 7800, 8800, DX600 Series, White
CP-DX-W-CORD=	Spare Handset Cord for Cisco IP Phone 8800, DX600 Series, White
CP-8800-WMK=	Spare Wallmount Kit for Cisco IP Phone 8800 Series
CP-8800-FS=	Spare Foot stand for Cisco IP Phone 8800 Series
CP-8800-B-BEZEL=	Spare Black Bezel for Cisco IP Phone 8800 Series
CP-8800-S-BEZEL=	Spare Silver Bezel for Cisco IP Phone 8800 Series
CP-PWR-CUBE-4	Cisco Power Cube 4
CP-PWR-CORD-AP=	Power Cord Asia Pacific
CP-PWR-CORD-AR=	Power Cord Argentina
CP-PWR-CORD-AU=	Power Cord Australia
CP-PWR-CORD-BZ=	Power cord for Brazil
CP-PWR-CORD-CE=	Power Cord European
CP-PWR-CORD-CN=	Power Cord China
CP-PWR-CORD-JP=	Power Cord Japan
CP-PWR-CORD-NA=	Power Cord North America
CP-PWR-CORD-SW=	Power Cord Switzerland
CP-PWR-CORD-UK=	Power Cord United Kingdom

## Warranty

The Cisco IP Phone 8841 phones are covered by a Cisco standard 1-year replacement warranty.

#### Cisco Unified Communications Services

Cisco and our certified partners can help you set up a secure, dependable Cisco Unified Communications Solution, meeting aggressive deployment schedules and accelerating business advantage. Cisco's portfolio of services is based on proven methodologies for unifying voice, video, data, and mobile applications on fixed and mobile networks.

Our unique lifecycle approach to services defines what's needed at each phase of the solution lifecycle. Customized planning and design services help you create a solution that meets your business needs. Awardwinning technical support helps you boost your operational efficiency. Remote management services simplify day-to-day operations. And optimization services let you modify and improve your network solution when business needs change.

#### Cisco Capital

#### Financing to Help You Achieve Your Objectives

Cisco Capital can help you acquire the technology you need to achieve your objectives and stay competitive. We can help you reduce CapEx. Accelerate your growth. Optimize your investment dollars and ROI. Cisco Capital financing gives you flexibility in acquiring hardware, software, services, and complementary third-party equipment. And there's just one predictable payment. Cisco Capital is available in more than 100 countries. Learn more.

#### More Information

For additional details about the Cisco IP Phone 8800 Series, go to http://www.cisco.com/go/ipphones/8800.



Contact us for more information or a consultation

TheMaynardGroup.com 800.377.3150

Printed in USA C78-731638-07 11/15